




Đèn hồng ngoại (iR - 3rd) thế hệ mới không phát sáng

Item	Picture	Parameters(English)	Price More10pcs	Brown Box size(cm)	Net weight (Kg)
GM IR100A WL100A		Φ4bucket IR illuminator, IR output 1,800mW @ 850nm, indoor/outdoor, 30-40m, 30°half power angle/60°full power angle, DC12V / AC24V shift automatic	68	17*10*12	0.3
GM IR100B WL100B		Φ4bucket IR illuminator, IR output2,400mW @ 850nm, indoor/outdoor, 50-60m, 22°half power angle/45° full power angle, DC12V / AC24V shift automatic	78	17*10*12	0.3
GM IR100C WL100C		Φ6bucket IR illuminator, IR output 2,800mW @ 850nm, indoor/outdoor, 70-80m, 15° half power angle/30°full power angle, DC12V / AC24V shift automatic	109	21*12*14	0.5
GM IR100D WL100D		Φ6bucket IR illuminator, IR output3,600mW @ 850nm, indoor/outdoor, 90-100m, 15°half power angle /30°full power angle, DC12V / AC24V shift automatic	120	21*12*14	0.5
GM IR100DE WL100DE		2.5"globosity IR illuminator, IR output 1,800mW @ 850nm, indoor, 50-60m2 , DC12V / AC24V shift automatic	70	15*15*12	0.5
GM IR100DM WL100DM		2.5"globosity IR illuminator,IR output2,400mW @ 850nm, indoor, DC12V / AC24V shift automatic,70-90m ²	81	15*15*12	0.5
GM IR100DR WL100DR		2.5"globosity IR illuminator,IR output2,800mW @ 850nm, indoor, DC12V / AC24V shift automatic, 100-120m ²	88	15*15*12	0.5
GM JR100A		Φ4bucket IR illuminator,IR output 2,500mW @ 940nm,(No visible infrared)outdoor,30-40m, 30°/60°/90° power angle, DC12V / AC24V shift automatic	81	17*10*12	0.3
GM JR100B		Φ4bucket IR illuminator,IR output 3,000mW @ 940nm,(No visible infrared)outdoor,40-50m, 22°power angle, DC12V / AC24V shift automatic	94	17*10*12	0.3
GM JR100C		Φ6bucket IR illuminator, 4,000mW @ 940nm, (No visible infrared) outdoor, 60 - 70m, 15° power power angle, DC12V / AC24V shift automatic	130	21*12*14	0.5
GM JR100D		Φ6bucket IR illuminator, 5,000mW @ 940nm, (No visible infrared) outdoor, 70 - 80m, 15° power angle, DC12V / AC24V shift automatic	99	21*12*14	0.5

GM JR100E		Φ6bucket IR illuminator, 6,000mW @ 940nm, (No visible infrared) outdoor, 80 – 90m, 15° power angle, DC12V / AC24V shift automatic	179	21*12*14	0.5
GM JR100DE		2.5"globosity IR illuminator, IR output 2,500mW @940nm,(No visible infrared) indoor, DC12V / AC24V shift automatic, 120°power angle,50–60m2,	73	15*15*12	0.5
GM JR100DM		2.5"globosity IR illuminator, IR output 3,000mW @940nm,(No visible infrared) indoor, DC12V / AC24V shift automatic, 120°power angle,70–80m ²	86	15*15*12	0.5
GM JR100DR		2.5"globosity IR illuminator, IR output 4,000mW @940nm, (No visible infrared) indoor, DC12V / AC24V shift automatic, 120°power angle,90 –100m2	99	15*15*12	0.5
GM IR300I		Flat Panel IR illuminator(outdoor), IR output 9, 000mW @ 850nm, outdoor, fix with high speed dome camera/uniform speed dome camera, 40-50m, 30° Half power angle/60° Full power angle.	312	22*14.8*15.5	2
GM IR300J		Flat panel IR illuminator, IR output 12, 000mW @ 850nm, outdoor, fix with high speed dome camera/uniform speed dome camera, 60-70m, 30° Half power angle/60° Full power angle.	367	22*14.8*15.5	2
GM IR300K		Flat panel IR illuminator, IR output 18, 000mW @ 850nm, outdoor, fix with high speed dome camera/uniform speed dome camera, 80-90m, 22° Half power angle/45° Full power angle.	424	22*14.8*15.5	2

Điều Kiện Thương Mại

Hàng hóa mới 100%

Báo giá chưa bao gồm thuế VAT - Miễn Phí giao hàng Nội Thành Hà Nội hoặc trên 20C với các tỉnh

Bảo hành theo tiêu chuẩn nhà sản xuất 12 Tháng

-Quý khách có yêu cầu liên hệ để biết thêm chi tiết về Sản phẩm, Giá và Bảo hành xin vui lòng liên hệ số Hotline Tel: 04. 858 22 606

Hoặc gửi thư đến địa chỉ: Sales@gmax.com.vn